

Code: VI-1500/LCD

UPS VI-1500/LCD 1500 VA

Net: 777.60 PLN Gross: 956.45 PLN

The VI-1500/LCD is a professional device, which providing stable power to connected sets of equipment. Additionally protects the connected equipment against overvoltages.



SPECIFICATION

Nominal power:	900 W
Power:	1500 VA
Input voltage:	162 ... 290 V AC
Output voltage:	230 V AC (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Charging time (recover to 90% capacity):	4 ... 6 hours
Backup time:	18 minutes
Battery:	2 x 12V/9Ah
Number of outputs:	2 pcs
Number of inputs:	2 pcs
Transfer time:	2 ... 6 ms (max. 10 ms)
Management software:	ViewPower (Polish version - Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)
Additional protection:	RJ11, RJ45
Protections:	<ul style="list-style-type: none">• Overcharge• Discharge• Short-circuit
Main features:	<ul style="list-style-type: none">• Short-time charging• Excellent microprocessor control guarantees high reliability• Built-in AVR voltage stabilization system• Auto restart while AC is recovering• Battery charging at power-off mode• "Cold Start" function• USB interface• Energy Saving function (possibility to deactivate from software)
Application:	to Home & Small Office applications
Operation state indication:	LCD display: operation mode, battery charging level, in/out voltage level
Housing type:	Tower

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


Dimensions:	397 x 147 x 205 mm
Weight:	10.52 kg
Guarantee:	2 years

PRESENTATION

Device connectors:



Example of displayed information:



In the kit:





DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60