

Code: AT-UPS2000RT-RACK

UPS AT-UPS2000RT-RACK 2000 VA EAST

Net: 533.60 EUR Gross: 656.33 EUR

The AT-UPS2000RT-RACK UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device is mounted to RACK 19" cabinet.

The device is a power supply of the online type and provides advanced mode of operation in total separation from the external mains. Thanks to this, it completely isolates connected devices and performs in practice the function of preventive protection against phenomena accompanying dynamic changes in mains parameters. These power supplies generate current transferred from the battery, which is constantly charged.

The device works with power supply adapters having Active Power Factor Correction (APFC).



SPECIFICATION

| | |
|--|---|
| Nominal power: | 1800 W |
| Power: | 2000 VA |
| Input voltage: | 230 V AC \pm 25 % |
| Input frequency: | 50 / 60 Hz (auto detection) |
| Output voltage: | 230 V AC \pm 5 % (Pure Sine Wave) |
| Output frequency: | 50 / 60 Hz \pm 1 % |
| Voltage adjustment: | \pm 1 % |
| Frequency adjustment: | <input type="checkbox"/> |
| Transfer time: | 0 ms |
| Charging time (recover to 90% capacity): | 8 hours |
| Battery: | 4 x 12V/9Ah |
| Number of outputs: | 2 pcs CEE 7/3 (Schuko) |
| Management software: | UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux) |
| Protections: | <ul style="list-style-type: none">• Glass Fuse• Overvoltage• Overload protection• EPO (Emergency power off) switch• Ethernet filter |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|--------------------------------------|---|
| Operation state indication: | <ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling |
| Main features: | <ul style="list-style-type: none"> • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Excellent microprocessor control guarantees high reliability • UPS auto diagnostic system • Battery charge and maintenance control • USB/RS-232 communication port |
| Application: | <ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment |
| Housing type: | Rack/Tower 2-in-1 Design |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 0 ~ 90 % (non-condensing) |
| Weight: | 22 kg |
| Dimensions: | 440 x 88 x 658 mm ; RACK 19", 2U |
| Manufacturer / Brand: | EAST |
| Guarantee: | 2 years |

PRESENTATION

UPS is equipped with large readable LCD display:



Rear view:



In the kit:

