

Code: VI-3000-RT/LCD

## UPS VI-3000-RT/LCD 3000 VA

Net: 2 630.88 PLN Gross: 3 235.98 PLN

The VI-3000-RT/LCD is a professional device, which providing stable power to connected sets of equipment. Additionally protects the connected equipment against overvoltages.



### SPECIFICATION

Nominal power:	2700 W
Power:	3000 VA
Input voltage:	161 ... 276 V AC
Input frequency:	50 / 60 Hz $\pm$ 5 % at standard mode > 40 Hz at generator mode
Output voltage:	220 / 230 / 240 V AC (Pure Sine Wave)
Voltage adjustment:	$\pm$ 5 % RMS for whole range of battery voltages
Frequency adjustment:	$\pm$ 0.1 % (battery mode)
Backup time:	4 minutes (at full load)
Charging time (recover to 90% capacity):	4 hours
Battery:	6 x 12V/9Ah
Number of outputs:	8 pcs
Transfer time:	2 ... 6 ms (max. 10 ms) (13ms at generator mode)
Additional protection:	RJ11, RJ45
Management software:	WinPower (Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)
Protections:	<ul style="list-style-type: none"><li>• Overload protection</li></ul>

Main features:	<ul style="list-style-type: none"> <li>• GreenPower UPSTM Technology</li> <li>• EPO (Emergency power off) function</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• UPS auto diagnostic system</li> <li>• Smart battery charging to extend battery lifetime</li> <li>• Intelligent cooler system control to reduce the noise level</li> <li>• Auto restart and charging</li> <li>• USB/RS-232 communication port</li> <li>• LCD, audio messages</li> <li>• Alarms indication on LCD: blue, red, blinking red based on UPS status</li> <li>• 4 x ICE C13 programmable outlets</li> <li>• Battery charging at power-off mode</li> <li>• "Cold Start" function</li> <li>• Energy Saving function (possibility to deactivate from software)</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• medium-sized enterprise</li> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>
Housing type:	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ~ 90 % (non-condensing)
Dimensions:	438 x 608 x 86.5 mm
Weight:	30.4 kg
Guarantee:	2 years

## PRESENTATION

UPS is equipped with large readable LCD display:



Device connectors:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60