

Code: ITC413-PW4D-IZ3

IP CAMERA ANPR **ITC413-PW4D-IZ3** - 4 Mpx 8 ... 32 mm - MOTOZOOM DAHUA

Net: **1 339.61 EUR** Gross: **1 339.61 EUR**

The IP ANPR (Automatic Number Plate Recognition) Camera is designed for auto recognition of the vehicle number plates.

The used motozoom lens with 8 ... 32 mm focal length allows to remote view angle adjustment.

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/1.8 " Progressive Scan CMOS
Matrix size:	4 Mpx
Resolution:	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	8 ... 32 mm - Motozoom
View angle:	40 ° ... 15 °
Range of IR illumination:	20 m
Compression:	H.265 / H.264 / MJPEG
Main stream frame rate:	25 fps - 4 Mpx
Network interface:	100/1000 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, TCP, ARP, RTSP, RTP, RTCP, UDP, SMTP, FTP, DHCP, DNS, NTP, SFTP, DDNS, SNMP, PPPoE
WEB Server:	Built-in
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Alarm inputs / outputs:	2 / 2
Audio:	• Microphone built-in, • External microphone input • Audio output • Bi-directional audio streaming support • Speaker built-in

RS-485 interface:	✓
Wiegand interface:	26 bit
Mobile phones support:	—
Main features:	• Motozoom lens • WDR - 140 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • ICR - Movable InfraRed filter • Day/night mode • Alarm notifications - Red and blue LEDs + Speaker • Built-in LPR Deep learning engine • Remote control - 868 MHz (included) • IVS analysis : intrusion, detection of loitering in a given area - support for 4 independent detection areas • Maximum vehicle speed for image analysis function : 120 km/h • Image analysis : License plate recognition, vehicle type recognition, vehicle brand and model recognition, vehicle color recognition, vehicle logo, detection of vehicles without a license plate, overlaying the image with time, address (channel position), lane (number/direction), plate (number and color), vehicle (speed, color, type)
Power supply:	• PoE (802.3at), • 12 V DC
Power consumption:	≤ 17 W
Housing:	Compact, Aluminum alloy + Plastic
Color:	Gray + Black
"Index of Protection":	IP67
Vandal-proof:	IK10
Operation temp:	-30 °C ... 65 °C
Weight:	2.34 kg
Dimensions:	396 x 121 x 128 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years


PRESENTATION



Side view:



Bottom view:



Mounting side view:



Camera bracket:



Connectors:



Dimensions:



See how to initialize DAHUA cameras:

:

In the kit:



OUR OPINIONS



- Motozoom lens.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

