

Code: APS-612

BUFFERED SWITCHING POWER SUPPLY ADAPTER **APS-612** SATEL

Net: **230.33 EUR** Gross: **283.31 EUR**

Buffered power adapter with DIN montage casing designed to systems supplied by 12V DC voltage. The APS-612 has a special connector that enables cooperation with SateL devices.



SPECIFICATION

| | |
|------------------------------|---|
| Adapter type: | Switching |
| Input voltage: | 230 V AC |
| Output voltage: | 12 V DC |
| Max. output current (total): | 6 A |
| Power: | 72 W |
| Battery charging current: | 1.5 A / 3 A |
| Protections: | <ul style="list-style-type: none">• Short-circuit• Reverse polarity connection• Overload• Overvoltage |
| Adapter operation control: | <ul style="list-style-type: none">• DC output voltage presence indication• Battery charging indication• AC input voltage presence indication• WS output - indicating AC power collapse• WB output - Low battery voltage• WP output Current overload indication |
| Housing type: | Plastic, DIN, TS-35 rail mounting |
| Weight: | 0.48 kg |
| Dimensions: | 79 x 123 x 90 mm |
| Manufacturer / Brand: | SATEL |
| Guarantee: | 2 years |

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Internal view, after remove the cover:



Adapter connectors (after remove the cover):



Side view:



Mounting side view:



In the kit:

