

Code: APS-612

BUFFERED SWITCHING POWER SUPPLY ADAPTER **APS-612** SATEL

Net: **267.98 EUR** Gross: **267.98 EUR**

Buffered power adapter with DIN montage casing designed to systems supplied by 12V DC voltage. The APS-612 has a special connector that enables cooperation with Satel devices.



SPECIFICATION

Adapter type:	Switching
Input voltage:	230 V AC
Output voltage:	12 V DC
Max. output current (total):	6 A
Power:	72 W
Battery charging current:	1.5 A / 3 A
Protections:	<ul style="list-style-type: none">• Short-circuit• Reverse polarity connection• Overload• Overvoltage
Adapter operation control:	<ul style="list-style-type: none">• DC output voltage presence indication• Battery charging indication• AC input voltage presence indication• WS output - indicating AC power collapse• WB output - Low battery voltage• WP output Current overload indication
Housing type:	Plastic, DIN, TS-35 rail mounting
Weight:	0.48 kg
Dimensions:	79 x 123 x 90 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Internal view, after remove the cover:



Adapter connectors (after remove the cover):



Side view:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

