

Code: APS-412

## BUFFERED SWITCHING POWER SUPPLY ADAPTER **APS-412** SATEL

Net: **58.92 EUR** Gross: **72.47 EUR**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment. The APS-412 has a special connector that enables cooperation with Satel devices.



### SPECIFICATION

Adapter type:	Switching
Input voltage:	230 V AC
Output voltage:	12 V DC
Max. output current (total):	4 A
Power:	48 W
Battery charging current:	0.5 A / 1 A
Protections:	<ul style="list-style-type: none"><li>• Short-circuit</li><li>• Reverse polarity connection</li><li>• Overload</li><li>• Overvoltage</li></ul>
Adapter operation control:	<ul style="list-style-type: none"><li>• DC output voltage presence indication</li><li>• Battery charging indication</li><li>• AC input voltage presence indication</li><li>• WS output - indicating AC power collapse</li><li>• WB output - Low battery voltage</li><li>• WP output Current overload indication</li></ul>
Housing type:	Plastic, DIN, TS-35 rail mounting
Weight:	0.28 kg
Dimensions:	79 x 123 x 60 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Adapter connectors:



Side view:



Mounting side view:



In the kit:

