

Code: HAC-HDW1400T-Z-A-2712

AHD, HD-CVI, HD-TVI, PAL CAMERA **HAC-HDW1400T-Z-A-2712** - 3.7 Mpx
2.7 ... 12 mm - **MOTOZOOM** DAHUA
Net: **473.00 PLN** Gross: **581.79 PLN**



Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.
The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.
The used motozoom lens with 2.7 ... 12 mm focal length allows to remote view angle adjustment.

SPECIFICATION

Standard:	AHD / HD-CVI / HD-TVI / CVBS
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	4 Mpx
Resolution:	2560 x 1440 - 3.7 Mpx @ 15 fps , 1920 x 1080 - 1080p @ 25 fps , 1280 x 720 - 720p , 960 x 576 - 960H, PAL
Lens:	2.7 ... 12 mm - Motozoom - The camera does not have auto-focus function
View angle:	• 92 ° ... 29 ° (manufacturer data) • 90 ° ... 30 (our tests result)
S/N ratio:	> 65 dB
Range of IR illumination:	60 m
IR illuminator power adjustment:	Automatic
Video output:	AHD / HD-CVI / HD-TVI / PAL - 1 Vpp / 75 Ω
Audio:	Microphone built-in - HD-CVI only
Main features:	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Auto White Balance • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/night mode
OSD menu:	OSD menu available via DAHUA recorder



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Power supply:	12 V DC / 660 mA
Power consumption:	≤ 8 W
Housing:	Dome, Aluminum
Color:	White
"Index of Protection":	IP67
Vandal-proof:	<input type="checkbox"/>
Operation temp:	-30 °C ... 60 °C
Weight:	0.58 kg
Dimensions:	Ø 122 x 104 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Camera view after remove the Dome cover:



Mounting side view:




In the kit:



OUR TESTS

AHD:


Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-CVI:

Camera image at artificial illumination (about 30Lux):







Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:

