

Code: ATE-CAM-AHD539HD

## AHD MOBILE CAMERA **ATE-CAM-AHD539HD** - 1080p 2.8 mm AUTONE

Net: **181.00 PLN** Gross: **222.63 PLN**



The ATE-CAM-AHD539HD camera is designed for installation outside vehicles.

The AHD interface allows to transmission of analog, composite video signal via coaxial cable. During transmission there are no delays and is maintained the original, high quality image.

Camera is according to IP67 Index of Protection norm.

### SPECIFICATION

Standard:	AHD
Sensor:	1/3 " Sony CMOS IMX323
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm
View angle:	89 ° (manufacturer data) 86 ° (our tests result)
Range of IR illumination:	10 m
S/N ratio:	≥ 58 dB
Video output:	1 Vpp / 75 Ω - M12, 4-pin socket, Code A
Audio:	—
Main features:	<ul style="list-style-type: none"><li>• AGC - Automatic Gain Control</li><li>• BLC - Back Light Compensation</li><li>• Auto White Balance</li><li>• Sharpness - sharper image outlines</li></ul>
OSD menu:	—
Housing:	Dome, Metal
Color:	Black
Application:	The camera is designed for installation outside vehicles
Power supply:	12 V DC / 420 mA - Powering the cameras with 12V DC voltage directly from recorder

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Power consumption:	< 5 W
Operation temp:	-10 °C ... 50 °C
Weight:	0.19 kg
Dimensions:	58 x 73 x 50 mm
Manufacturer / Brand:	AUTONE
Guarantee:	2 years

## PRESENTATION

Small dimensions camera:



Front view:



Rear view:



Camera dimensions:





In the kit:



## OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



#### OUR OPINIONS



- Solid workmanship.

