

Code: VT03211D-P2-S2

## VIDEO DOORPHONE **VT03211D-P2-S2** DAHUA

Net: **255.31 EUR** Gross: **314.03 EUR**

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.



### SPECIFICATION

Compatibility:	DAHUA
Sensor:	1/2.8", 2 Mpx CMOS
View angle:	129 °
Image compression method:	H.264
Resolution:	<ul style="list-style-type: none"><li>• Main stream : 800 x 480, 1280 x 720, 720 x 576</li><li>• Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240</li></ul>
IR illuminator:	✓
proximity reader built-in:	Access control cards - Mifare S50
The number of subscribers served:	2
Main features:	<ul style="list-style-type: none"><li>• It can only work with the mobile application, without the VTH monitor</li><li>• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel</li><li>• Bidirectional communication,</li><li>• Microphone built-in,</li><li>• Speakers built-in,</li><li>• Echo suppression and reduction / digital noise reduction,</li><li>• Tamper detection - opening the enclosure,</li><li>• Vandal-proof front panel,</li><li>• Output for the additional lock release button,</li><li>• WDR - 120 dB - Wide Dynamic Range,</li><li>• Motion Detection</li></ul>
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">DMSS</a></li><li>• iOS (iPhone): Free application <a href="#">DMSS</a></li></ul>

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Power supply:	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 1 A</li> </ul>
Power consumption:	<ul style="list-style-type: none"> <li>≤ 7 W (operation)</li> <li>≤ 1 W (Standby mode)</li> </ul>
Housing:	Aluminum alloy, Waterproof
Color:	Graphite
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Mechanical strength:	IK08
Operation temp:	-30 °C ... 60 °C
Weight:	0.48 kg
Dimensions:	182 x 101 x 32 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>

## PRESENTATION

Front view:



Side view:



Rear view:



Connectors view:



Connection schematic diagram:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60