

Code: VTO3311Q-WP

WIRELESS VIDEO DOORPHONE **VTO3311Q-WP** Wi-Fi / IP DAHUA

Net: **295.10 EUR** Gross: **362.97 EUR**



The device works with video doorphones, and other DAHUA panels. The Wi-Fi / IP Video Doorphone allows to remote control of the electromagnetic lock using smartphone or tablet. It can only work with the mobile application, without the VTH monitor. The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel.

Attention! To play back recordings from the memory card installed in the VTO3311Q-WP, the VTH monitor is required.

Video Doorphone is mounted in a surface housing.

SPECIFICATION

Compatibility:	DAHUA
The number of subscribers served:	4
Sensor:	1/2.8 ", 2 Mpx CMOS
View angle:	125 °
Image compression method:	H.265 / H.264
Resolution:	<ul style="list-style-type: none">• Main stream : 1280 x 720, 800 x 480, 720 x 576, 352 x 288• Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288, 320 x 240
LED illuminator:	—
IR illuminator:	✓
PIR detector:	—
proximity reader built-in:	Access control cards - 13.56 MHz S50
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface:	<ul style="list-style-type: none">• Ethernet 10 / 100 Mbps• Wi-Fi
RS-485 interface:	✓



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> • Micro SD memory cards up to 256GB support (possible local recording), • Unlocking by card, application or indoor monitor, • Voice call and unlock the door directly from the mobile app., • Remote configuration, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 2D-DNR, 3D-DNR - Digital Noise Reduction, • Day/Night mode (color/b&w/auto), • ICR - Movable InfraRed filter, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Vandal-proof front panel, • LED diodes, • Alarm inputs / outputs : 1 / 1, • Output for the additional lock release button, • Power output, • Rain cover included
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1 A
Power consumption:	<ul style="list-style-type: none"> ≤ 6 W (operation) ≤ 3 W (Standby mode)
Housing:	Aluminum alloy, Waterproof
Color:	Graphite
"Index of Protection":	IP65
Mechanical strength:	IK08
Operation temp:	-40 °C ... 60 °C
Weight:	0.6 kg
Dimensions:	<ul style="list-style-type: none"> • 188 x 107 x 30 mm (without cover) • 191 x 112 x 44 mm (with cover)
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front view:



Side view:




Rear view:




Connectors:



Dimensions:



Example of application:



1. INDOOR PANEL
2. VIDEO DOORPHONE
3. Switch PoE
4. Router
5. Remote client

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60