

Code: DS-KIS202

VIDEO DOORPHONE KIT **DS-KIS202** Hikvision

Net: **565.00 PLN** Gross: **694.95 PLN**

Video Doorphone set of the Hikvision brand with a door station mounted in a surface housing and a 7" colored screen. The DS-KIS202 doesn't need any additional configuration (after connecting according to the diagram the device is ready to operate).

ATTENTION! The device does not support the HIKVISION IP system.



SPECIFICATION

DOOR STATION:	
Sensor:	1/4 " CMOS
IR illuminator:	<input type="checkbox"/>
proximity reader built-in:	<input type="checkbox"/>
Video output:	1 Vpp, CVBS - pair of wires compatible with HIKVISION analog video door-phone system
Operation temp:	-30 °C ... 60 °C
Power supply:	12 V DC
Power consumption:	≤ 3 W (operation)
Main features:	<ul style="list-style-type: none">• Relay output• 4-wire cable installation : 5 m (included)
Housing:	Aluminum / Plastic, Waterproof
Color:	Black / Silver
"Index of Protection":	IP65
Weight:	0.15 kg
Dimensions:	135 x 49 x 41 mm
INDOOR PANEL:	
Shield:	7 " TFT-LCD color matrix
Resolution:	800 x 480
Main features:	<ul style="list-style-type: none">• Plug & Play,• Ultra-flat hands-free monitor, with speakerphone,• Smooth volume control,• Microphone built-in,• Speakers built-in,• Bidirectional communication
Power supply:	12 V DC

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Max. current:	420 mA
Power consumption:	≤ 5 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.278 kg
Dimensions:	196 x 133 x 18 mm
Manufacturer / Brand:	Hikvision
SAP Code:	305300619
Guarantee:	3 years

PRESENTATION

Door station:

Front view:



Side view:



Particular elements:



Rear view:



Connectors:



INDOOR PANEL:

Front view:



Rear view:



Connectors:



Volume adjustment:



In the kit:

