

Code: DS-KD-M

PROXIMITY READER MODULE **DS-KD-M** Hikvision

Net: **313.00 PLN** Gross: **384.99 PLN**

The DS-KD-M module is designed to work with the DS-KD8003-IME1 or DS-KD8003-IME2 video doorphone module.

Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings). The masking frames attached to the housings of both series are made of aluminum.



SPECIFICATION

Cards support:	MIFARE 13.56 MHz
Reading distance of prox-keys:	max. 5 cm
Autonomous operation:	—
Keyboard built-in:	—
Doorbell button:	—
Tamper output:	—
Compatibility:	DS-KD8003-IME1 , DS-KD8003-IME2
Power supply:	Supplied by DS-KD8003-IME1 or DS-KD8003-IME2
Power consumption:	≤ 2 W
Permissible relative humidity:	10 ... 95 % (non-condensing)
"Index of Protection":	IP65
Housing:	Plastic
Color:	Black
Operation temp:	-40 °C ... 60 °C
Weight:	0.17 kg
Dimensions:	100 x 98 x 34 mm
Manufacturer / Brand:	Hikvision

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

SAP Code:	305301208
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:



Connectors view:



Example of application:

