

Code: DS-KB8113-IME1

VIDEO DOORPHONE **DS-KB8113-IME1** Hikvision

Net: **168.82 EUR** Gross: **207.65 EUR**



Video doorphone is designed to work with Hikvision II generation indoor IP panels.

SPECIFICATION

Sensor:	2 Mpx, 1080p
Camera view angle:	87 ° (manufacturer data)
Camera resolution:	<ul style="list-style-type: none">• 1920 x 1080 px - 1080p• 1280 x 720 px - 720p
Image compression method:	H.264
LED illuminator:	—
IR illuminator:	Range : 3 m
Compatibility:	Hikvision IP Video Doorphones
proximity reader built-in:	—
UTP category:	UTP cat. 5e
Alarm inputs:	1 pcs
Relay outputs:	1 pcs NO/NC
RS-485:	—
Ethernet:	1 x RJ-45 - 10/100 Base-T

Main features:	<ul style="list-style-type: none"> • True WDR - Wide Dynamic Range, • Motion Detection, • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Echo suppression and reduction / digital noise reduction • Remote configuration - Web browser • The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel
Operation temp:	-30 °C ... 50 °C
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC
Housing:	Metal, Waterproof, Vandal-proof - IK09
"Index of Protection":	IP65
Color:	Black
Weight:	0.8 kg
Dimensions:	162 x 74 x 54 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305302014
Guarantee:	3 years

PRESENTATION

Particular elements:



Device connectors:



Connectors description:



Rear view:



In the kit:

