Code: DS-KIS701-W-D

# VIDEO DOORPHONE KIT **DS-KIS701-W-D** Hikvision

Net: 524.27 EUR Gross: 524.27 EUR

Two-wire HIKVISION video doorphones system with 7" touch monitor and controller enabling connection and supply of up to 9 groups of devices. Video Doorphone is mounted in a flush-mounted housing.
The device has the ability to work with the Hik-Connect application for mobile devices.
The attached DS-KAD709 controller also enables the connection of the video doorphone system to the LAN network and via it to the Internet.



**SPECIFICATION**

| | |
|---|---|
| Sensor: | 2.1 Mpx CMOS |
| Image compression method: | H.264 |
| LED illuminator: | – |
| IR illuminator: | ✔ |
| Compatibility: | HIKVISION 2-wire Video Doorphones |
| Main features: | • Doorbell button,<br>• Bidirectional communication,<br>• Microphone built-in,<br>• Speakers built-in,<br>• Tamper detection - removing from mounting surface,<br>• LEDs for system state indication and user interface display,<br>• Door contact and request button for exit inputs,<br>• The device has the ability to work with the Hik-Connect application for mobile devices,<br>• Relay output : NO/NC |
| Operation temp: | -30 °C ... 60 °C |
| Power supply: | 24 V DC - via DS-KAD709 |
| Housing: | Metal, Waterproof |
| Color: | Silver |
| "Index of Protection": | IP65 |
| Weight: | 0.79 |
| Dimensions: | 169 x 110 x 52 |

INDOOR PANEL:

| | |
|---|---|
| Shield: | 7 " capacitive touch screen |
| Resolution: | 1024 x 600 |
| Internal memory: | – |
| Memory card slot: | SD memory cards up to 32GB support (possible local recording) |
| Mobile phones support: | • Android: Free application Hik-Connect<br>• iOS (iPhone): Free application Hik-Connect |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|---|---|
| Default administrator password: | 888999 |
| Main features: | • Microphone built-in,<br>• Speakers built-in,<br>• Bidirectional communication,<br>• Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,<br>• Automatically capture and save images if there is no response to the doorbell,<br>• Support for capturing a photo during video calls,<br>• Register a short voice message if there is no response to the bell button,<br>• Full support via network,<br>• LEDs for system state indication and user interface display,<br>• Possibility to connect up to 3 compatible devices (door stations, internal panels, KAD-709 controller),<br>• IP Hikvision cameras support |
| Controlling: | One-touch action buttons + capacitive touch screen |
| Alarm inputs: | — |
| Power supply: | 24 V DC - via DS-KAD709 |
| Color: | White |
| Weight: | 0.514 kg |
| Dimensions: | 196 x 133 x 21 mm |

ENCLOSURE:

| | |
|---|---|
| Housing type: | Flush-mounted |
| Material: | Metal |
| Color: | Black |
| Internal dimensions: | 160 x 101 x 37 mm |
| External dimensions: | 162 x 103 x 38 mm |

**Controller:**

| | |
|---|---|
| Network interface: | RJ45 - 10/100 Base-T |
| Number of supported devices: | max. 9 pcs |
| Device powering: | ✔ |
| Power supply: | 24 V DC<br>(power adapter included) |
| Housing: | Plastic, DIN, TS-35 rail mounting |
| Color: | White |
| Weight: | 0.20 |
| Dimensions: | 110 x 112 x 66 |

General information:

| | |
|---|---|
| Supported languages: | Polish, English, Czech, French, Spanish, Dutch, German, Romanian, Hungarian, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 305301533 |
| Guarantee: | **3 years** |

**PRESENTATION**

INDOOR PANEL:




Mounting side view:




Connectors:




Memory card slot:




Video doorphone:




Mounting side view:



Connectors:



HIKVISION
Villa Door Station
Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.
Address: No.555 Qianmo Road, Binjiang District,
Hangzhou 310052, China
Importer: Hikvision Europe B.V.
Address: Dirk Storklaan 3, 2132 PX Hoofddorp,The Netherlands
NC NO COM GND
DOOR
485
IO1 IO2 12V GND PLC PLC
OUTPUT



**Controller**:




Mounting side view:




Connectors:







Power adapter:



Mounting side view:




Connectors:






Examples of connection diagrams:




1. Video doorphone
2. Controller
3. INDOOR PANEL
4. 24V DC power adapter
5. Electromagnetic Lock
6. Router
7. Remote client

A 1-pair cable
B UTP cat. 5
In the kit:



**PACKAGE**

| | |
|---|---|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |