

Code: DS-KIS602(B)(O-STD)

VIDEO DOORPHONE KIT **DS-KIS602(B)(O-STD)** Hikvision

Net: **512.33 EUR** Gross: **630.17 EUR**

HIKVISION video doorphone set with 7" touch monitor and with the possibility of integration with both the alarm system and video monitoring. Video Doorphone is mounted in a surface housing.

Attention! To ensure proper operation, the "Extend" switch of the switch included in the set should be in the "Off" position.



SPECIFICATION

Compatibility:	IP Hikvision video doorphones II generation
Doorbell button:	1 pcs
Sensor:	2.1 Mpx CMOS
Camera resolution:	1920 x 1080 - 1080p
Camera view angle:	146 °
Image compression method:	H.264
IR illuminator:	✓
Ethernet:	10/100 Mb/s
Network protocols:	TCP/IP, RTSP
Alarm inputs:	4 pcs
Relay outputs:	2 x NO/NC
Main features:	<ul style="list-style-type: none">• Bidirectional communication,• Microphone built-in,• Speakers built-in,• Noise suppression and echo cancellation,• Tamper detection - removing from mounting surface,• Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings)• Power output : 12 V DC / 500 mA (max)
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC
Power consumption:	≤ 5 W
Operation temp:	-40 °C ... 60 °C
Housing:	Metal
Color:	Black

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

"Index of Protection":	IP65
Weight:	0.38 kg
Dimensions:	100 x 98 x 44 mm

INDOOR PANEL:

Compatibility:	IP Hikvision modular video doorphones
Shield:	7 " - capacitive touch screen
Resolution:	1024 x 600
Internal memory:	128 MB (built-in)
Main features:	<ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB, 16 GB included • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices
Controlling:	capacitive touch screen
Default administrator password:	— The administrator password should be set at the first start
Default password for securing the zone:	—
Alarm inputs:	8
Alarm outputs:	2
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC
Power consumption:	≤ 6 W
Color:	Black + Silver
Operation temp:	-10 °C ... 55 °C
Weight:	0.34 kg
Dimensions:	200 x 140 x 25 mm

ENCLOSURE:

Number of mounted modules:	1 pcs
Material:	Aluminum
Color:	Graphite
Weight:	0.32 kg
External dimensions:	117 x 107 x 37 mm

SWITCH :

Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af
LAN ports:	<ul style="list-style-type: none"> • 1 x RJ45 100 Base-T - Uplink, • 4 x 10/100 Base-T (4 x PoE (802.3af))
LED diodes:	Power, PoE, Link/Act
Transmission speed:	10 / 100 Mbps : 1 Port LAN + 4 LAN & PoE ports
Management:	—




Maximal output power:	15 W / port PoE
Maximal total power:	38 W
MAC addresses table:	1k - Auto update of MAC addresses table
Operation modes:	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 - 1 ... 4 ports • Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6
Operation temp:	0 °C ... 40 °C
Power supply:	48 V DC / 800 mA (power adapter included)
Weight:	0.2 kg
Dimensions:	132 x 95 x 28 mm

General information:

Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305303906
Guarantee:	3 years

PRESENTATION

INDOOR PANEL:



Mounting side view:





Connectors:





Memory card slot:



VIDEO DOORPHONE:



Mounting side view:



Connectors:



SWITCH :



Connectors:






Power adapter:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------