

Code: UT-70A

UNIVERSAL METER UT-70A UNI-TNet: **64.01 EUR** Gross: **78.73 EUR**

The UT-70A is a universal digital meter used to measure: voltage, current, resistance, inductance, capacitance, frequency, hFE, temperature and checking the correctness of diodes operation.

SPECIFICATION

DC voltage measurement:	200 mV ± (0.5% + 1) @ 100 μV , 2 V ± (0.5% + 1) @ 1 mV , 20 V ± (0.5% + 1) @ 10 mV , 200 V ± (0.5% + 1) @ 100 mV , 1000 V ± (0.8% + 2) @ 1 V
AC voltage measurement:	200 mV ± (1.2% + 3) @ 100 μV , 2 V ± (0.8% + 3) @ 1 mV , 20 V ± (0.8% + 3) @ 10 mV , 200 V ± (0.8% + 3) @ 100 mV , 750 V ± (1.2% + 3) @ 1 V
DC current measurement:	20 μA ± (0.8% + 1) @ 0.01 μA , 2 mA ± (0.8% + 1) @ 1 μA , 200 mA ± (1.5% + 1) @ 0.1 mA , 10 A ± (2.0% + 5) @ 10 mA
AC current measurement:	20 μA ± (1.0% + 3) @ 0.01 μA , 2 mA ± (1.0% + 3) @ 1 μA , 200 mA ± (1.8% + 3) @ 0.1 mA , 10 A ± (3.0% + 7) @ 10 mA
Resistance measurement:	200 Ω ± (0.8% + 3) @ 0.1 Ω , 2 kΩ ± (0.8% + 1) @ 1 Ω , 20 kΩ ± (0.8% + 1) @ 10 Ω , 200 kΩ ± (0.8% + 1) @ 100 Ω , 2 MΩ ± (0.8% + 1) @ 1 kΩ , 20 MΩ ± (1.0% + 5) @ 10 kΩ , 2000 MΩ ± (5.0% + 10) @ 1 MΩ
Capacitance measurement:	20 nF ± (2.5% + 5) @ 10 pF , 200 nF ± (2.5% + 5) @ 100 pF , 2 μF ± (2.5% + 5) @ 1 nF , 100 μF ± (5.0% + 4) @ 100 nF
Inductance measurement:	2 mH ± (2.0% + 10) @ 1 μH , 20 mH ± (2.0% + 10) @ 10 μH , 200 mH ± (2.0% + 10) @ 0.1 mH , 20 H ± (3.0% + 10) @ 10 mH

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Frequency measurement:	2 kHz ... 10 MHz \pm (0.1% + 3) @ 1 Hz (automatic range change)
Temperature measurement:	<ul style="list-style-type: none"> • °C -40 ... 0 °C \pm (3% + 4) @ 1 °C 0 ... 400 °C \pm (1% + 3) @ 1 °C 400 ... 1000 °C \pm (2% + 10) @ 1 °C, • °F -40 ... 32 °F \pm (3% + 4) @ 1 °F 32 ... 752 °F \pm (1% + 4) @ 1 °F 752 ... 1832 °F \pm 2.5% @ 1 °F
hFE:	✓
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	✓
RS-232:	—
Main features:	<ul style="list-style-type: none"> • Large, readable LCD display with backlight • Aesthetic and solid construction
Power supply:	9V, type 6F22 battery - included
Dimensions:	205 x 101 x 60 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------