

Code: UT-33B+

UNIVERSAL METER UT-33B+ UNI-T

Net: 10.26 EUR Gross: 12.62 EUR



UT-33B+ is a universal digital meter used to measure: voltage, current, resistance. The device also has a built-in battery tester.

SPECIFICATION

DC voltage measurement:	200 mV ± (0.7% + 3) @ 0.1 mV , 2000 mV ± (0.5% + 2) @ 1 mV , 20 V ± (0.7% + 3) @ 10 mV , 200 V ± (0.7% + 3) @ 100 mV , 600 V ± (0.7% + 3) @ 1 V
AC voltage measurement:	200 V ± (1.2% + 3) @ 100 mV , 600 V ± (1.2% + 3) @ 1 V
DC current measurement:	200 μA ± (1% + 2) @ 0.1 μA , 200 mA ± (1% + 2) @ 100 μA , 10 A ± (1.2% + 5) @ 10 mA
AC current measurement:	—
Resistance measurement:	200 Ω ± (1% + 2) @ 0.1 Ω , 2 kΩ ± (0.8% + 2) @ 1 Ω , 20 kΩ ± (0.8% + 2) @ 10 Ω , 200 kΩ ± (0.8% + 2) @ 100 Ω , 20 MΩ ± (1.2% + 3) @ 10 kΩ , 200 MΩ ± (5% + 10) @ 100 kΩ
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	—
hFE:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	<ul style="list-style-type: none"> • Measurement of the battery discharge level: 12V, 9V, 1.5V • Large, readable LCD display with backlight • Freezing the last reading • Low battery level alarm • Aesthetic and solid construction
Power supply:	2 x 1.5V, type AAA/LR03 battery - included
Weight:	0.26 kg
Dimensions:	134 x 77 x 47 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



Place for batteries 2 x 1.5V AAA:



In the kit:

