

Code: UT-39B

UNIVERSAL METER **UT-39B** UNI-T

Net: **20.81 EUR** Gross: **20.81 EUR**



The UT-39B is a universal digital meter used to measure: voltage, current, resistance, capacitance, hFE, and checking the correct operation of diodes.

SPECIFICATION

DC voltage measurement:	200 mV $\pm$ (0.5% + 1) @ 0.1 mV , 2 V $\pm$ (0.5% + 1) @ 0.001 V , 20 V $\pm$ (0.5% + 1) @ 0.01 V , 200 V $\pm$ (0.5% + 1) @ 0.1 V , 1000 V $\pm$ (0.8% + 2) @ 1 V
AC voltage measurement:	2 V $\pm$ (0.8% + 3) @ 0.001 V , 20 V $\pm$ (0.8% + 3) @ 0.01 V , 200 V $\pm$ (0.8% + 3) @ 0.1 V , 750 V $\pm$ (1.2% + 3) @ 1 V
DC current measurement:	20 μ A $\pm$ (2.0% + 5) @ 0.01 μ A , 2 mA $\pm$ (0.8% + 1) @ 0.001 mA , 20 mA $\pm$ (0.8% + 1) @ 0.01 mA , 200 mA $\pm$ (1.5% + 1) @ 0.1 mA , 10 A $\pm$ (2.0% + 5) @ 0.01 A
AC current measurement:	2 mA $\pm$ (1.0% + 3) @ 0.001 mA , 200 mA $\pm$ (1.8% + 3) @ 0.1 mA , 10 A $\pm$ (3.0% + 5) @ 0.01 A
Resistance measurement:	200 Ω $\pm$ (0.8% + 3) @ 0.1 Ω , 2 k Ω $\pm$ (0.8% + 1) @ 0.001 k Ω , 20 k Ω $\pm$ (0.8% + 1) @ 0.01 k Ω , 2 M Ω $\pm$ (0.8% + 1) @ 0.001 M Ω , 20 M Ω $\pm$ (1.0% + 2) @ 0.01 M Ω , 200 M Ω $\pm$ (5%(RD-10) + 10) @ 0.1 M Ω * *RD - reading value
Capacitance measurement:	2 nF $\pm$ (4% + 3) @ 0.001 nF , 200 nF $\pm$ (4% + 3) @ 0.1 nF , 20 μ F $\pm$ (4% + 3) @ 0.01 μ F
Inductance measurement:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	—
hFE:	✓
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	• Large, readable LCD display with backlight • Freezing the last reading • Low battery level alarm • Aesthetic and solid construction
Power supply:	9V, type 6F22 battery - included
Weight:	0.32 kg
Dimensions:	172 x 83 x 41 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



Place for 9V battery:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------