

Code: UT-52

UNIVERSAL METER **UT-52** UNI-T

Net: **29.76 EUR** Gross: **36.60 EUR**

The UT-52 is a universal digital meter used to measure: voltage, current, resistance, capacitance, hFE, and checking the correct operation of diodes.



SPECIFICATION

DC voltage measurement:	200 mV ± (0.5% + 1) @ 0.1 mV , 2 V ± (0.5% + 1) @ 0.001 V , 20 V ± (0.5% + 1) @ 0.01 V , 200 V ± (0.5% + 1) @ 0.1 V , 1000 V ± (0.8% + 2) @ 1 V
AC voltage measurement:	200 mV ± (1.2% + 3) @ 0.1 mV , 2 V ± (0.8% + 3) @ 0.001 V , 20 V ± (0.8% + 3) @ 0.01 V , 200 V ± (0.8% + 3) @ 0.1 V , 750 V ± (1.2% + 3) @ 1 V
DC current measurement:	2 mA ± (0.8% + 1) @ 0.001 mA , 20 mA ± (0.8% + 1) @ 0.01 mA , 200 mA ± (1.5% + 1) @ 0.1 mA , 20 A ± (2.0% + 5) @ 0.01 A
AC current measurement:	2 mA ± (1.0% + 3) @ 0.001 mA , 20 mA ± (1.0% + 3) @ 0.01 mA , 200 mA ± (1.8% + 3) @ 0.1 mA , 20 A ± (3.0% + 7) @ 0.01 A
Resistance measurement:	200 Ω ± (0.8% + 3) @ 0.1 Ω , 2 kΩ ± (0.8% + 1) @ 0.001 kΩ , 20 kΩ ± (0.8% + 1) @ 0.01 kΩ , 200 kΩ ± (0.8% + 1) @ 0.1 kΩ , 2 MΩ ± (0.8% + 1) @ 0.001 MΩ 20 MΩ ± (1.0% + 2) @ 0.01 MΩ , 200 MΩ ± (5%(RD-10) + 10) @ 0.1 MΩ * *RD - reading value

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Capacitance measurement:	2 nF ± (4% + 3) @ 0.001 nF , 20 nF ± (4% + 3) @ 0.01 nF , 200 nF ± (4% + 3) @ 0.1 nF , 2 μF ± (4% + 3) @ 0.001 μF , 20 μF ± (4% + 3) @ 0.01 μF
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	—
hFE:	✓
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	<ul style="list-style-type: none"> • Large, readable LCD display • Low battery level alarm • Aesthetic and solid construction
Power supply:	9V, type 6F22 battery - included
Weight:	0.5 kg
Dimensions:	203 x 98 x 56 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



The device is equipped with a height-adjustable support:



Place for 9V battery:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

