

Code: UT-20B

## UNIVERSAL METER UT-20B UNI-T

Net: 7.03 EUR Gross: 7.03 EUR

UT-20B is a universal digital meter used to measure: voltage, current, resistance. The device also has a built-in battery tester.



### SPECIFICATION

DC voltage measurement:	200 mV $\pm$ (1.5% + 2) @ 0.1 mV , 2000 mV $\pm$ (2.5% + 2) @ 1 mV , 20 V $\pm$ (2.5% + 2) @ 10 mV , 200 V $\pm$ (2.5% + 2) @ 100 mV , 300 V $\pm$ (2.5% + 2) @ 1 V
AC voltage measurement:	200 V $\pm$ (2.5% + 15) @ 100 mV , 300 V $\pm$ (2.5% + 15) @ 1 V
DC current measurement:	2000 $\mu$ A $\pm$ (2.5% + 10) @ 1 $\mu$ A , 20 mA $\pm$ (2.5% + 10) @ 10 $\mu$ A , 200 mA $\pm$ (2.5% + 10) @ 100 $\mu$ A
AC current measurement:	—
Resistance measurement:	200 $\Omega$ $\pm$ (2.5% + 5) @ 0.1 $\Omega$ , 2000 $\Omega$ $\pm$ (2.5% + 5) @ 1 $\Omega$ , 20 k $\Omega$ $\pm$ (2.5% + 5) @ 10 $\Omega$ , 200 k $\Omega$ $\pm$ (2.5% + 5) @ 100 $\Omega$ , 2000 k $\Omega$ $\pm$ (2.5% + 5) @ 1 k $\Omega$
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	—
hFE:	—
Diode test:	✓
Sound signal of the continuity test:	—
Checking TTL logic states:	—
RS-232:	—

Main features:	<ul style="list-style-type: none"> <li>• Measurement of the battery discharge level: 9V, 1.5V,</li> <li>• Large, readable LCD display,</li> <li>• Low battery indicator,</li> <li>• Aesthetic and solid construction,</li> <li>• Built-in rectangular signal source with a frequency of 50 Hz and an output resistance of 47 kΩ</li> </ul>
Power supply:	12V, type A23 battery - included
Weight:	0.08 kg
Dimensions:	94 x 55 x 29 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

## PRESENTATION

Front panel:



The product has a very small dimensions:



Place for 12V A23 battery:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60