

Code: UT-256B

CLAMP METER (OPEN CLAMPS) **UT-256B** UNI-T

Net: **83.63 EUR** Gross: **83.63 EUR**



The UT-256B is a universal digital meter equipped with open clamps enabling the measurement of high currents. The device measures: voltage, current, resistance and capacity. In addition, the meter has an electric field detection function (NCV).

The meter is equipped with the True RMS transducer enabling accurate measurement of the RMS current and voltage for both sinusoidal and distorted waveforms.

SPECIFICATION

DC voltage measurement:	6 V ± (0.8% + 3) @ 0.001 V , 60 V ± (0.8% + 3) @ 0.01 V , 600 V ± (0.8% + 3) @ 0.1 V , 1000 V ± (1% + 5) @ 1 V
AC voltage measurement:	6 V ± (1.2% + 5) @ 0.001 V , 60 V ± (1.2% + 3) @ 0.01 V , 600 V ± (1.2% + 3) @ 0.1 V , 750 V ± (1.5% + 5) @ 1 V
DC current measurement:	200 A ± (2.5% + 5) @ 0.1 A
AC current measurement:	200 A ± (2.5% + 5) @ 0.1 A
Resistance measurement:	600 Ω ± (1.2% + 2) @ 0.1 Ω , 6 kΩ ± (1% + 2) @ 0.001 kΩ , 60 kΩ ± (1% + 2) @ 0.01 kΩ , 600 kΩ ± (1% + 2) @ 0.1 kΩ , 6 MΩ ± (1.2% + 2) @ 0.001 MΩ , 60 MΩ ± (1.5% + 5) @ 0.01 MΩ
Capacitance measurement:	60 nF ± (4% + 20) @ 0.01 nF , 600 nF ± (4% + 20) @ 0.1 nF , 6 μF ± (4% + 20) @ 0.001 μF , 60 μF ± (4% + 20) @ 0.01 μF , 600 μF ± (4% + 20) @ 0.1 μF , 6 mF ± (10%) @ 0.001 mF 60 mF @ 0.01 mF
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	✓
Diode test:	✓

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Sound signal of the continuity test:	✓
RS-232:	—
USB:	—
Main features:	<ul style="list-style-type: none"> • True RMS - accurate measurement of the RMS current and voltage for any waveform, • NCV - electric field detection function, • REL - relative measurement mode, • Freezing the highest or lowest measurement, • Hold - stopping the meter reading, • Flashlight built-in, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case
Power supply:	2 x 1.5V, type AA/LR6/FR6 battery - included
Weight:	0.18 kg
Dimensions:	210 x 53 x 35 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION



Side view:



Bottom view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Place for batteries 2 x 1.5V AA:



Device is secured by handy case:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

