

Code: UT-P3315-TFL-II

## LABORATORY POWER SUPPLY **UT-P3315-TFL-II** UNI-T

Net: **76.54 EUR** Gross: **94.14 EUR**

The UT-P3315-TFL-II laboratory power supply allows you to generate a constant voltage or current with strictly defined parameters. The device can work in one of two modes: as a source of constant voltage or as a source of constant current.



### SPECIFICATION

Output voltage range of the power adapter:	0 V ... 30 V
Power supply output current range:	0 A ... 5 A
Output power:	160 W
Setting resolution:	<ul style="list-style-type: none"><li>• Voltage : 10 mV @ 25 °C ± 5 °C</li><li>• Current : 1 mA @ 25 °C ± 5 °C</li></ul>
Setting accuracy:	<ul style="list-style-type: none"><li>• Voltage : &lt; 0.5 % + 20 mV @ 20 Hz ... 20 MHz</li><li>• Current : &lt; 0.5 % + 10 mA @ 20 Hz ... 20 MHz</li></ul>
Ripple and noise:	<ul style="list-style-type: none"><li>• Voltage : ≤ 2 mV RMS</li><li>• Current : ≤ 3 mA RMS</li></ul>
Temperature coefficient:	<ul style="list-style-type: none"><li>• Voltage : ≤ 300 ppm/°C</li><li>• Current : ≤ 300 ppm/°C</li></ul>
Response time:	< 100 μs
Number of outputs:	1
Display:	LED display Double
Power supply:	230 V AC / 110 V AC - selectable by switch
Operation temp. / Relative humidity:	0 °C ... 40 °C / ≤ 85 %
Weight:	4.06 kg
Dimensions:	255 x 165 x 105 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

## PRESENTATION

Front view:



Rear view:





In the kit:

