

Code: UT-P3315-TFL-II

LABORATORY POWER SUPPLY **UT-P3315-TFL-II** UNI-T

Net: **103.17 EUR** Gross: **103.17 EUR**

The UT-P3315-TFL-II laboratory power supply allows you to generate a constant voltage or current with strictly defined parameters. The device can work in one of two modes: as a source of constant voltage or as a source of constant current.



SPECIFICATION

Output voltage range of the power adapter:	0 V ... 30 V
Power supply output current range:	0 A ... 5 A
Output power:	160 W
Setting resolution:	<ul style="list-style-type: none">• Voltage : 10 mV @ 25 °C ± 5 °C• Current : 1 mA @ 25 °C ± 5 °C
Setting accuracy:	<ul style="list-style-type: none">• Voltage : < 0.5 % + 20 mV @ 20 Hz ... 20 MHz• Current : < 0.5 % + 10 mA @ 20 Hz ... 20 MHz
Ripple and noise:	<ul style="list-style-type: none">• Voltage : ≤ 2 mV RMS• Current : ≤ 3 mA RMS
Temperature coefficient:	<ul style="list-style-type: none">• Voltage : ≤ 300 ppm/°C• Current : ≤ 300 ppm/°C
Response time:	< 100 μs
Number of outputs:	1
Display:	LED display Double
Power supply:	230 V AC / 110 V AC - selectable by switch
Operation temp. / Relative humidity:	0 °C ... 40 °C / ≤ 85 %
Weight:	4.06 kg
Dimensions:	255 x 165 x 105 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PRESENTATION

Front view:



Rear view:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------