Code: UT-P3313-TFL-II

LABORATORY POWER SUPPLY **UT-P3313-TFL-II** UNI-T

Net: 96.18 EUR Gross: 96.18 EUR

The UT-P3313-TFL-II laboratory power supply allows you to generate a constant voltage or current with strictly defined parameters. The device can work in one of two modes: as a source of constant voltage or as a source of constant current.



SPECIFICATION

Output voltage range of the power adapter:	0 V ... 30 V
Power supply output current range:	0 A ... 3 A
Output power:	96 W
Setting resolution:	• Voltage : 10 mV @ 25 °C ± 5 °C • Current : 1 mA @ 25 °C ± 5 °C
Setting accuracy:	• Voltage : < 0.5 % + 20 mV @ 20 Hz ... 20 MHz • Current : < 0.5 % + 10 mA @ 20 Hz ... 20 MHz
Ripple and noise:	• Voltage : ≤ 2 mV RMS • Current : ≤ 3 mA RMS
Temperature coefficient:	• Voltage : ≤ 300 ppm/°C • Current : ≤ 300 ppm/°C
Response time:	< 100 µs
Number of outputs:	1
Display:	LED display - Double
Power supply:	230 V AC / 110 V AC - selectable by switch
Operation temp. / Relative humidity:	0 °C ... 40 °C / ≤ 85 %
Weight:	3.3 kg
Dimensions:	255 x 165 x 105 mm
Manufacturer / Brand:	UNI-T

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg