

Code: UT-18C

## VOLTAGE AND PHASE SEQUENCE INDICATOR **UT-18C** UNI-T

Net: **49.80 EUR** Gross: **49.80 EUR**



The UT-18C meter allows to measure AC, DC voltages in the range 12 ... 690V. The measurement is carried out automatically when the probes come into contact with the measuring points. The device automatically selects the appropriate measuring range and informs the user about it using LEDs located above the display.

In addition to measuring the voltage, the device allows you to check the continuity of the circuit and measure the phase shift between the two phases of power supply.

### SPECIFICATION

|                                          |                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LCD display:                             | ✓                                                                                                                                                                                                                                                                                                                                                                    |
| DC voltage measurement:                  | Illustrative measurement : <ul style="list-style-type: none"><li>• 12 V,</li><li>• 24 V,</li><li>• 50 V,</li><li>• 120 V,</li><li>• 230 V,</li><li>• 400 V,</li><li>• 690 V</li></ul>                                                                                                                                                                                |
| AC voltage measurement:                  | Illustrative measurement : <ul style="list-style-type: none"><li>• 12 V,</li><li>• 24 V,</li><li>• 50 V,</li><li>• 120 V,</li><li>• 230 V,</li><li>• 400 V,</li><li>• 690 V</li></ul>                                                                                                                                                                                |
| Phase sequence detection:                | ✓                                                                                                                                                                                                                                                                                                                                                                    |
| DC voltage polarization detection:       | ✓                                                                                                                                                                                                                                                                                                                                                                    |
| Sound signal of the continuity test:     | 0 ... 100 kΩ                                                                                                                                                                                                                                                                                                                                                         |
| Resistance measurement:                  | —                                                                                                                                                                                                                                                                                                                                                                    |
| Frequency measurement:                   | 40 Hz ... 400 Hz                                                                                                                                                                                                                                                                                                                                                     |
| RCD test (residual current device test): | ✓                                                                                                                                                                                                                                                                                                                                                                    |
| Main features:                           | <ul style="list-style-type: none"><li>• Sound signaling</li><li>• Over-voltage indicator</li><li>• Voltage tester function (one probe measurement using the contact placed on it) - Detection of voltage above 100V results in lighting the diode</li><li>• Low battery indicator</li><li>• Flashlight built-in</li><li>• Aesthetic and solid construction</li></ul> |





Rear view:



Place for batteries 2 x 1.5V AAA:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|