

Code: DP-HD36-NS1

IP CAMERA **DP-HD36-NS1** Tuya Smart Wi-Fi - 1080p 3.6 mm

Net: **37.14 EUR** Gross: **45.68 EUR**

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 100 m.

Attention! Camera for indoor use only. Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/3 Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	3.6 mm
View angle:	<ul style="list-style-type: none">• 130 ° (manufacturer data)• 80 ° (our tests result)
Range of IR illumination:	10 m
Audio:	<ul style="list-style-type: none">• Microphone built-in,• Speaker built-in,• Audio transmission via network,• Bi-directional audio streaming support
Image compression method:	H.265
Network interface:	Wi-Fi - IEEE 802.11 b/g/n
ONVIF:	—
WEB Server:	—
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none">• The Tuya Smart free application on Android• The Tuya Smart free application on iOS
Default IP address:	DHCP

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 100 m (open area) • Motion Detection - Built-in PIR detector • micro USB socket • RESET button
Power supply:	<ul style="list-style-type: none"> • 18650 battery - 2 pcs, • 5 V DC / 1 A (power adapter not included) or USB
Power consumption:	<ul style="list-style-type: none"> ≤ 1.3 W (operation) ≤ 1 mW (Standby mode)
Housing:	Plastic
"Index of Protection":	—
Weight:	0.2 kg
Dimensions:	63 x 78 x 89 mm
Operation temp:	-10 °C ... 55 °C
Supported languages:	English
Guarantee:	2 years

PRESENTATION

Small dimensions camera:



Rear view:



Memory card slot, micro USB and "Reset" button:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- Small dimensions of the camera.