

Code: APTI-W22R2-TUYA

## IP CAMERA **APTI-W22R2-TUYA** Wi-Fi - 1080p 3.6 mm

Net: **296.08 PLN** Gross: **364.18 PLN**



The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 30 m.

**Attention!** Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.

### SPECIFICATION

Standard:	TCP/IP
Sensor:	Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 720 - 720p
Lens:	3.6 mm
View angle:	<ul style="list-style-type: none"><li>• 85 ° (manufacturer data)</li><li>• 81 ° (our tests result)</li></ul>
Range of IR illumination:	30 m
White light LED illuminator range:	30 m
Audio:	<ul style="list-style-type: none"><li>• Microphone built-in,</li><li>• Speaker built-in,</li><li>• Audio transmission via network,</li><li>• Bi-directional audio streaming support</li></ul>
Image compression method:	Smart H.264
Network protocols:	TCP/IP, P2P
Network interface:	<ul style="list-style-type: none"><li>• Wi-Fi - IEEE 802.11 b/g/n</li><li>• 100 Base-T</li></ul>
ONVIF:	—
WEB Server:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>
Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	<ul style="list-style-type: none"> <li>• Wi-Fi Module - IEEE 802.11 b/g/n, Range : 30 m (open area)</li> <li>• Video PUSH personal messaging</li> <li>• Motion Detection</li> <li>• At night, the default mode is IR, while when motion detection is triggered, the LED illuminator turns on, and after another 45s it automatically changes to IR</li> <li>• The white LED light can be remotely turned on/off via the app</li> <li>• Sound signaling</li> <li>• ICR - Movable InfraRed filter</li> <li>• RESET button</li> </ul>
Power supply:	12 V DC / 840 mA (power adapter included)
Power consumption:	≤ 10 W
Housing:	Plastic + Metal
"Index of Protection":	IP66
Weight:	0.3 kg
Dimensions:	54 x 214 x 48 mm
Operation temp:	-20 °C ... 55 °C
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years

## PRESENTATION





Memory card slot, micro USB and "Reset" button:



Mounting side view:





In the kit:



Sample interface screenshot:





## OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in LED illuminator on:



Camera image at night conditions with internal built-in IR illuminator on:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------