

Code: APTI-W21R2S-TUYA

IP CAMERA APTI-W21R2S-TUYA Tuya Smart Wi-Fi - 1080p 3.6 mm

Net: **82.40 EUR** Gross: **82.40 EUR**

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 30 m.

Attention! Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 640 x 360
Lens:	3.6 mm
View angle:	<ul style="list-style-type: none">• 90 ° (manufacturer data)• 76 ° (our tests result)
Range of IR illumination:	—
White light LED illuminator range:	15 m
Audio:	<ul style="list-style-type: none">• Microphone built-in,• Speaker built-in,• Audio transmission via network,• Bi-directional audio streaming support
Image compression method:	H.264
Main stream frame rate:	25 fps
Network protocols:	TCP/IP
Network interface:	Wi-Fi - IEEE 802.11 b/g/n
ONVIF:	—
WEB Server:	—
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none">• The Tuya Smart free application on Android• The Tuya Smart free application on iOS
Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 30 m (open area) • Day/night mode • ICR - Movable InfraRed filter • Motion Detection - Built-in PIR detector • Operation status LED indicator • RESET button
Power supply:	<ul style="list-style-type: none"> • built-in battery, • Solar Panel : 5 W, • 5 V DC - micro USB socket (power adapter not included)
Power consumption:	<ul style="list-style-type: none"> ≤ 0.75 W (operation) ≤ 0.0025 W (Standby mode)
Housing:	Plastic
"Index of Protection":	IP65
Weight:	<ul style="list-style-type: none"> • 0.33 kg (camera) • 0.52 kg (solar panel)
Dimensions:	<ul style="list-style-type: none"> • 209 x 74 x 42 mm (camera) • 265 x 174 x 12 mm (solar panel)
Operation temp:	-10 °C ... 60 °C
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Front view:



Mounting side view:



Bottom view:



Solar Panel:





Solar panel connector:




Connection method:



In the kit:



Sample interface screenshot:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in LED illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------