

Code: TL-WR940N

ROUTER **TL-WR940N** 2.4 GHz 450 Mbps TP-LINK

Net: **21.78 EUR** Gross: **26.79 EUR**

The TL-WR940N wireless router offers 4 ports of 10/100 Mb/s and wireless data transmission with speed up to 450 Mb/s.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. With 3T3R MIMO™ Technology, the device creates an exceptional and advanced wireless performance, making it ideal for streaming HD video, VoIP and online gaming.

Easy wireless security encryption at a push of WPS button. IP based bandwidth control allows administrators to determine how much bandwidth is allotted to each PC.



SPECIFICATION

Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	3 x 5 dBi
Standards:	IEEE 802.11 b/g/n
Baud rates:	450 Mbps
LAN ports:	1 x 10/100 Mbps Uplink 4 x 10/100 Mbps LAN
LED indicators:	Power, WLAN, Act/Link (4 x Ethernet), WAN, WPS
Receiver sensitivity:	<ul style="list-style-type: none">• 270M: -68dBm@10% PER• 130M: -68dBm@10% PER• 108M: -68dBm@10% PER• 54M: -68dBm@10% PER• 11M: -85dBm@8% PER• 6M: -88dBm@10% PER• 1M: -90dBm@8% PER
DDNS:	<ul style="list-style-type: none">• No-IP• DynDNS• Comexe
DHCP server:	✓
Firmware update:	✓
Operation modes:	Router, Range Extender, Access Point
Protections:	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface:	Web browser, TP-LINK Tether

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Transmitter power:	max. 20 dBm
Power supply:	9 V DC / 0.6 A (power adapter included)
Main features:	<ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.278 kg
Dimensions:	230 x 144 x 35 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION

Top view:



Device connectors:



In the kit:

