

Code: ARCHER-VR400

ACCESS POINT +ROUTER **ARCHER-VR400** VDSL / ADSL 300 Mbps + 867 Mbps

Net: **76.49 EUR** Gross: **94.08 EUR**

The ARCHER-VR400 router has been designed for sharing Internet connection provided by ADSL / VDSL technology. It has built-in ADSL / VDSL modem compatible with ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2, Access Point works in IEEE802.11 b/g/n @ 2.4 GHz, IEEE802.11 a/n/ac @ 5 GHz standards enabling transmission speed up to 300 Mb/s @ 2.4 GHz, 867 Mb/s @ 5 GHz and 4-port switch. The device has a DSL connector in the form of RJ-11 port.

The ARCHER-VR400 ensures advanced access control and NAT, its DHCP server supports static assignment of IP addresses. The device also supports virtual servers, DMZ zone, remote logging and management.

The USB 2.0 port enables connection the additional peripherals, such as the 3G/4G modem, or an external hard drive.



SPECIFICATION

| | |
|-----------------------|---|
| Frequency range: | <ul style="list-style-type: none">• 2.4 GHz,• 5 GHz |
| Standards: | IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5 |
| LAN ports: | 3x RJ-45 (10/100 Mbps, Auto MDI/MDX) 1x RJ-45 (10/100/1000 Mbps, Auto MDI/MDX) |
| WAN interface: | 1x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 |
| Transmitter power: | < 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz |
| Baud rates: | 300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz |
| DHCP server: | ✓ |
| Firmware update: | ✓ |
| DDNS: | ✓ |
| Protections: | <ul style="list-style-type: none">• LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL• WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES |
| Management interface: | Web browser |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|--------------------------------|---|
| Main features: | <ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • 1 x Port USB 2.0 • The DSL line splitter included |
| Operation temp: | 0 °C ... 40 °C |
| Permissible relative humidity: | max. 90 % (max) |
| Power supply: | 12 V DC / 1.5 A (power adapter included) |
| Weight: | 0.32 kg |
| Dimensions: | 216 x 125 x 32 mm |
| Manufacturer / Brand: | TP-LINK |
| Guarantee: | 2 years |

PRESENTATION



Rear panel:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60