

Code: DS-3WF01C-2N

ACCESS POINT + Customer Premises Equipment **DS-3WF01C-2N** Hikvision

Net: **255.95 EUR** Gross: **255.95 EUR**

The DS-3WF01C-2N set, designed to work in elevators, has a housing resistant to high temperatures and ensures stable operation in very difficult conditions. The set includes an access point and a client station.

The devices work in 802.11 b/g/n standard, and in addition they are equipped with 2x2 MIMO efficient antennas.

Each device is additionally equipped with 2 LAN ports for connecting two more devices and has one PoE port that allows you to power the device and connect it to the LAN network.



SPECIFICATION

Frequency range:	2412 MHz ... 2472 MHz
Antenna type:	2Tx 2Rx MIMO 6 dBi Integrated
Standards:	• IEEE 802.11 b/g/n
LAN ports:	3 x 10/100 Mbps BASE-TX (Cat. 5, RJ-45)
Receiver sensitivity:	• -72 dBm @ 65 Mbps • -97 dBm @ 1 Mbps
Operation modes:	Access Point, Access Point Client, Access Point WDS, WDS client
Transmitter power:	27 dBm
Horizontal beam width (H):	65 °
Vertical beam width (V):	60 °
Main features:	Operates in configuration Point-to-Point and Point-to-Multipoint
Power supply PoE:	✓
Power supply:	12 V / 1 A (power adapter included)
Operation temp:	-30 °C ... 65 °C
Permissible relative humidity:	5 % ... 95 %
Weight:	0.23 kg - Transmitter / Receiver
Dimensions:	150 x 150 x 44 mm - Transmitter / Receiver

Manufacturer / Brand:	Hikvision
SAP Code:	301801029
Guarantee:	3 years

PRESENTATION

Front view:



Connectors:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------