

Code: TL-EAP230-WALL

ACCESS POINT **TL-EAP230-WALL** 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK

Net: 72.47 EUR Gross: 72.47 EUR

Wireless Wall-Plate Access Point. The design of the device enables easy wall mounting in a standard junction box. Placing the EAP device in each room ensures an exclusive, high-speed Wi-Fi connection for every user.

Free Omada Controller Software enables to centrally manage of wireless network.

Enterprise class Wi-Fi security help to decrease network security threats. Device allows to secure data transmission using the encryption protocols: WEP, WPA/WPA2 and WPA-PSK/WPA2-PSK (64/128/152 bits).



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	• 2.4 GHz : 2 x 4 dBi Integrated, Omnidirectional antenna , • 5 GHz : 2 x 3.6 dBi Integrated, Omnidirectional antenna
Polarization:	vertical/horizontal
Standards:	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
Baud rates:	2.4 GHz : max. 300 Mbps (dynamic) + 5 GHz : max. 867 Mbps (dynamic)
Protections:	WEP 64/128/152-bit, WPA / WPA2-Enterprise, WPA-PSK/WPA2-PSK
LAN ports:	2 x 10/100/1000 Mbps
Management interface:	Web browser, Omada application
Transmitter power:	< 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz
Housing:	Plastic
Power supply PoE:	✓
Power supply:	PoE (802.3af/at)
Power consumption:	7 W
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 %

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Main features:	• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Omada Central Management System • Software Omada Controller • 200 on-line users • Multi-SSID (max. 16) • Load balance • QoS - mechanisms, which provide the high quality of transmission • Enable/Disable Wireless Radio • Wireless transmission statistics • Wireless Network Schedule • Authentication using the welcome page • Access control • MAC addresses filtering • Wireless isolation between clients • SSID to VLAN mapping • Rogue Access Point detection • 802.1x Radius • Watchdog built-in • e-mail personal messaging • Power supply PoE • LED/WiFi button • RESET button
Weight:	0.124 kg
Dimensions:	87 x 87 x 30 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	5 years

PRESENTATION

Front view:




View without the front cover:



Mounting side view:



Transmission schematic diagram:



1. INTERNET
2. Router
3. Switch PoE
4. Access Point (AP)
5. System management center
6. clients

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------