

Code: RG-EG105G-P-V2

## ROUTER **RG-EG105G-P-V2**, 4 PoE REYEE

Net: **162.56 EUR** Gross: **162.56 EUR**

The RG-EG105G-P-V2 Gigabit VPN Router supports many VPN protocols, providing high performance and high security. Operation integrated with the Ruijie Cloud platform enables central management from the cloud and Ruijie Reyee application.

2 Gigabit Ethernet WAN ports with bandwidth load balance raise the utilization rate of multi-line broadband.



### SPECIFICATION

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards:             | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at                                                                                                                                                                                                                                                                                                                                                                               |
| LAN ports:             | <ul style="list-style-type: none"><li>• 3 x LAN &amp; PoE 10/100/1000 Mbps (RJ-45)</li><li>• 1 x LAN &amp; PoE / WAN 10/100/1000 Mbps (RJ-45)</li></ul>                                                                                                                                                                                                                                                                                                |
| WAN interface:         | <ul style="list-style-type: none"><li>• 1 x WAN x 10/100/1000 Mbps (RJ-45)</li></ul>                                                                                                                                                                                                                                                                                                                                                                   |
| LED indicators:        | Status, Link/Act                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| DDNS:                  | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| DHCP server:           | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Port USB:              | —                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Firmware update:       | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power supply PoE:      | Power output - LAN ports : PoE (802.3af/at) max. 54 W (total)                                                                                                                                                                                                                                                                                                                                                                                          |
| Protections:           | <ul style="list-style-type: none"><li>• ACL</li><li>• IP-MAC Binding</li><li>• MAC addresses filtering</li><li>• Support for dynamic ARP mapping and static table</li><li>• NAT / NAPT</li><li>• Port Mapping</li></ul>                                                                                                                                                                                                                                |
| Management interface:  | <ul style="list-style-type: none"><li>• Ruijie Cloud Central Management System</li><li>• Configuration using the Ruijie Reyee application</li><li>• Remote management</li><li>• Web browser</li></ul>                                                                                                                                                                                                                                                  |
| Mobile phones support: | Android: Free application <a href="#">Ruijie Reyee</a><br>iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>                                                                                                                                                                                                                                                                                                                                  |
| Main features:         | <ul style="list-style-type: none"><li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li><li>• Static / dynamic routing</li><li>• WAN : PPPoE, PPTP, L2TP</li><li>• DHCP client/server support</li><li>• Access Control List - ACL package filtering based on source and destination IP addresses</li><li>• Rate limit</li><li>• Load balance</li><li>• NAT</li><li>• View topology and network status</li><li>• RESET button</li></ul> |
| Power supply:          | 54 V DC / 1.15 A (power adapter included)                                                                                                                                                                                                                                                                                                                                                                                                              |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                |                                |
|--------------------------------|--------------------------------|
| Power consumption:             | max. 60 W (at full load)       |
| Operation temp:                | 0 °C ... 40 °C                 |
| Permissible relative humidity: | 10 % ... 90 % (non-condensing) |
| Weight:                        | 0.43 kg                        |
| Dimensions:                    | 207 x 109 x 28 mm              |
| Manufacturer / Brand:          | RUIJIE / REYEE                 |
| Guarantee:                     | 2 years                        |

## PRESENTATION

Front panel:



Rear panel:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|