

Code: RG-AP820-L(V3)

ACCESS POINT **RG-AP820-L(V3)** Wi-Fi 6, SFP 2.4 GHz, 5 GHz, 547 Mbps + 2402 Mbps RUIJIE

Net: **283.64 EUR** Gross: **283.64 EUR**

The RG-AP820-L(V3) access point broadcasts 2 separate wireless networks in the 5 GHz band with speed 2402 Mb/s and in the 2.4 GHz band with speed 574 Mb/s. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

The product is used in service points, shops, in companies and at home. Wall or ceiling mounting.

Supports 802.11ax standard - the next generation of Wi-Fi.

Access Point is managed through the web and the cloud (Ruijie Reyee application).



SPECIFICATION

Frequency range:	• 2.4 GHz (2.4 ... 2.4835 GHz), • 5 GHz (5.150 ... 5.250, 5.250 ... 5.350, 5.470 ... 5.725, 5.725 ... 5.850 GHz) ,
Antenna type:	• 2x2 MU-MIMO - built-in • 2.8 dBi @ 2.4 GHz - 2 pcs • 3.6 dBi @ 5 GHz - 2 pcs
Standards:	• IEEE 802.11 b/g/n/ax @ 2.4 GHz, • IEEE 802.11 a/n/ac/ax @ 5 GHz
Baud rates:	547 Mbps @ 2.4 GHz + 2402 Mbps @ 5 GHz
LAN ports:	• 1 x 10 / 100 / 1000 Mbps Ethernet + PoE IN - RJ45, • 1 x 2.5 Gbps - SFP
Port USB:	—
LED indicators:	Power / System
DDNS:	—
DHCP server:	✓
Firmware update:	✓

Protections:	• WEP 64/128-bit, WPA-TKIP, WPA-PSK, WPA2 AES • IEEE 802.1x and Radius Authentication • Black list • Access Control List - ACL package filtering based on source and destination MAC addresses • CPP • NFPP • WIDS • SSID hiding
Operation modes:	Access Point
Management interface:	• Ruijie Cloud Central Management System • Configuration using the Ruijie Reyee application • Remote management • Web browser • Console - RJ-45 output
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Default IP address:	192.168.110.1
Transmitter power:	max. 26 dBm @ 2.4 GHz max. 26 dBm @ 5 GHz
Main features:	• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • OFDMA • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Load balance • WLAN : 32 x BSSID - 16 x Wireless BSSID • Multicast • IPv4/IPv6 - Static routing • ICMP • VPN support : IPsec, PPPoE • SNMPv1/v2c/v3(MIB-2) • Statistical Reporting, System logs • DHCP client • Bluetooth 5.1 interface • RESET button
Housing:	Plastic
Power supply PoE:	PoE (802.3af)
Power supply:	• 48 V DC / 0.6 A (not included) • PoE
Power consumption:	max. 12.95 W
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	0 % ... 95 % (non-condensing)
Weight:	• 0.61 kg (without bracket) • 0.67 kg (with bracket)
Dimensions:	220 x 220 x 52 mm (without bracket)
Manufacturer / Brand:	RUIJIE
Guarantee:	3 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:






Device connectors:



Side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

