

Code: TL-WR841N

ROUTER **TL-WR841N** 300 Mbps TP-LINK

Net: 20.27 EUR Gross: 20.27 EUR

The TL-WR841N is a wideband router (for xDSL service or cable modem) and 4-port FastEthernet switch.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.

The TL-WR841N ensures advanced access control and QoS, its DHCP server supports static assignment of IP addresses. The device also supports virtual servers, DMZ zone, remote logging and management.



SPECIFICATION

Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	2 x 5 dBi
Standards:	IEEE 802.11 b/g/n
Baud rates:	300 Mbps
Processor:	Atheros
Modulation type:	CCK, OFDM, BPSK, QPSK
LAN ports:	1 x 10/100 Mbps Uplink 4 x 10/100 Mbps LAN
LED indicators:	Power, System, LAN, WLAN, Act/Link (4 x Ethernet)
Receiver sensitivity:	• 270M: -68dBm@10% PER • 130M: -68dBm@10% PER • 108M: -68dBm@10% PER • 54M: -68dBm@10% PER • 11M: -85dBm@8% PER • 6M: -88dBm@10% PER • 1M: -90dBm@8% PER
DDNS:	• No-IP • DynDNS • Comexe
DHCP server:	✓
Firmware update:	✓
Operation modes:	Router, Bridge WDS

Protections:	64/128/152-bit WEP, WPA/WPA2 Table of access / access-deny according to MAC addresses of client cards Internet access filtering via filters of IP addresses, MAC addresses and ports of TCP/IP protocol
Management interface:	Web browser
Transmitter power:	max. 20 dBm
Power supply:	9 V DC / 600 mA (power adapter included)
Main features:	• MAC address cloning • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	max. 90 % (non-condensing)
Weight:	0.170 kg
Dimensions:	192 x 130 x 33 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION

Top view:



Device connectors:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------