

Code: PFWB5-10AC

CUSTOMER PREMISES EQUIPMENT **PFWB5-10AC** DAHUA

Net: **335.32 EUR** Gross: **412.44 EUR**



The PFWB5-10AC is an integrated solution for professional outdoor wireless networks. Thanks to a unique construction, device offers unparalleled performance in such a compact device.

The casing made of UV resistant plastic is resistant to even the most severe weather conditions.

SPECIFICATION

Frequency range:	5150 MHz ... 5850 MHz
Antenna type:	20 dBi, 2x2 MIMO - Bandwidth 5 GHz
Standards:	IEEE 802.11 a/n/ac
Baud rates:	max. 866 Mbps
LAN ports:	1 x 10/100/1000 Mbps
Vertical beam width (V):	10 °
Horizontal beam width (H):	10 °
Operation modes:	WDS client, TDMA client, WDS Base Station, TDMA Base Station, ARP NAT Base Station, Bridge, Router
Protections:	Overvoltage protection
Transmitter power:	30 dBm
Wireless transmission range:	<ul style="list-style-type: none">• Recommended ≤ 5 km• max. 7 km
Memory:	64 MB RAM, 16 MB Flash
Processor:	QCA9563 750 MHz
Power supply PoE:	✓
Power supply:	12 V ... 24 V DC - Passive PoE (power adapter included)
Power consumption:	10 W
Operation temp:	-30 °C ... 70 °C

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Weight:	0.41 kg
Dimensions:	187 x 185 x 81 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Rear view:




connector:



Power adapter:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------