

Code: RG-RAP6260(G)

ACCESS POINT **RG-RAP6260(G)** Wi-Fi 6 2.4 GHz, 5 GHz 574 Mbps + 1201 Mbps REYEE

Net: **398.94 EUR** Gross: **398.94 EUR**

The RG-RAP6260(G) access point broadcasts 2 separate wireless networks in the 5 GHz band with speed 1201 Mb/s and in the 2.4 GHz band with speed 574 Mb/s. The Access Point is designed for outdoor use, ensuring good connectivity in extreme weather environments over longer distances.

The product meets the IP68 tightness class.



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	2x2 MIMO, 2.4 GHz - 4 dBi / 5.0 GHz - 6 dBi, Integrated - Omnidirectional antenna
Standards:	IEEE 802.11 a/b/g/n/ac/ax
Baud rates:	2.4 GHz : max. 574 Mbps + 5 GHz : max. 1201 Mbps
Protections:	WPA-TKIP, WPA2 AES, WPA-PSK
LAN ports:	• 1 x 10/100/1000 Mbps RJ45 + PoE IN • 1 x 100/1000 Base-X port SFP
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Management interface:	Web browser, Ruijie Cloud
Transmitter power:	≤ 26 dBm @ 2.4 GHz ≤ 25 dBm @ 5 GHz
Housing:	Outdoor, plastic (Weatherproof)
Overvoltage protection:	6 kV lightning
Power supply PoE:	✓
Power supply:	PoE (802.3at)
Power consumption:	≤ 17 W
Operation temp:	-40 °C ... 65 °C

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Permissible relative humidity:	0 % ... 100 % (non-condensing)
Certificates:	CE, RoHS
Main features:	• Access Point is managed through the web and the cloud (Ruijie Reyee application) • Mobile phones support • Number of users : 512 (max) • Multi-SSID (max. 8) • Enable/Disable Wireless Radio • WMM (Wi-Fi Multimedia) • Transmit power control • Support for Reyee Mesh technology • Load balance • Rate limit • Wireless Network Schedule • Wireless transmission statistics • Access control • MAC addresses filtering • Wireless isolation between clients • LED indication • Power supply PoE • Easy to install on any wall or pole (mounting kit included) • Seamless Roaming - 802.11k/v roaming function switches clients automatically to the AP with the optimal signal with a seamless transition when moving. This allows sensitive applications like VoIP and video conferences to go uninterrupted
"Index of Protection":	IP68
Weight:	2 kg (without mounting kit)
Dimensions:	310 x 310 x 80 mm (without mounting kit)
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	3 years

PRESENTATION

Front view:



Mounting side view:




Device connectors:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------