

Code: PB-10

LATCHING PANIC BUTTON **PB-10** SATEL

Net: 13.62 EUR Gross: 13.62 EUR

This button is a device designed to instantly trigger the alarm and (or) initiate the procedure of reporting an emergency situation in protected facility to the monitoring station. The button can also be used to control various devices (e.g. automation or access control system devices).

The device can interface with any alarm control panel which supports the NC type detectors.



SPECIFICATION


Support:	Alarm control panels - input for connecting a NC type wired detector
Alarm output:	NC, 24 V DC / 100 mA
Tamper protection:	NC, 24 V DC / 10 mA
Main features:	• Application : Internal • Tamper detection - opening the enclosure, removing from mounting surface • Environmental class EN 50130-5 : II
Operation temp:	-10 °C ... 55 °C
Permissible relative humidity:	93 % ± 3 %
Weight:	0.052 kg
Dimensions:	Ø 97 x 29 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Rear view:



Internal view of the housing:



Description of particular elements of the device:



- 1. button
- 2. tamper contact
- 3. fixing screw hole
- 4. cable terminals
- TMP - TAMPER output
- NC - Alarm output
- 5. tamper contact



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------