

Code: 24V/0.5A/GPV

## SWITCHING ADAPTER **24V/0.5A/GPV**

Net: **6.64 EUR** Gross: **6.64 EUR**

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



### SPECIFICATION

Adapter type:	Switching
Power voltage:	90 ... 264 V AC
Frequency range:	47 ... 63 Hz
Output voltage:	24 V DC
Output voltage tolerance:	± 5 %
Maximal load:	0.5 A
Output power:	12 W
Efficiency:	79 %
Number of outputs:	1 pcs
Protections:	<ul style="list-style-type: none"><li>• Overload</li><li>• Short-circuit</li><li>• Overvoltage</li><li>• Overheat</li></ul>
Main features:	<ul style="list-style-type: none"><li>• Protection class : II</li><li>• Possibility to mount to the wall</li></ul>
Housing type:	Plastic, Waterproof
"Index of Protection":	IP67
Operation temp:	-30 °C ... 70 °C
Weight:	0.12 kg
Dimensions:	130 x 25 x 22 mm
Guarantee:	<b>3 years</b>

### PRESENTATION

Top view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------