

Code: 24V/2.5A/GPV-MINI

## SWITCHING ADAPTER 24V/2.5A/GPV-MINI

Net: 13.83 EUR Gross: 17.01 EUR

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



### SPECIFICATION

Adapter type:	Switching
Power voltage:	180 ... 264 V AC
Frequency range:	47 ... 63 Hz
Output voltage:	24 V DC
Output voltage tolerance:	± 3 %
Maximal load:	2.5 A
Output power:	60 W
Efficiency:	86 %
Number of outputs:	1 pcs
Protections:	<ul style="list-style-type: none"><li>• Overload</li><li>• Short-circuit</li><li>• Overvoltage</li></ul>
Main features:	<ul style="list-style-type: none"><li>• Protection class : II</li><li>• Box casing designed to wall mounting</li></ul>
Housing type:	Plastic, Waterproof
"Index of Protection":	IP67
Operation temp:	-20 °C ... 70 °C
Weight:	0.24 kg
Dimensions:	148 x 32 x 28 mm
Guarantee:	<b>3 years</b>

### PRESENTATION

Top view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



**PACKAGE**

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

