

Code: AT-UPS650-LCD

UPS AT-UPS650-LCD 650 VA EAST

Net: 63.97 EUR Gross: 63.97 EUR

The AT-UPS650-LCD UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device works with power supply adapters having Active Power Factor Correction (APFC).



SPECIFICATION

Nominal power:	390 W
Apparent Power:	650 VA
Input voltage:	165 V ... 275 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	\leq 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	1 pcs - 12V/7Ah
Estimated battery operation time:	<ul style="list-style-type: none">• 19 minutes @ 100 W• 6 minutes @ 200 W• 2 minutes @ 300 W
Number of outputs:	2 pcs CEE 7/3 (Schuko)
Protections:	<ul style="list-style-type: none">• Glass Fuse• Overvoltage• Overload protection• Overcharge protection• Telephone line filter
Operation state indication:	<ul style="list-style-type: none">• LCD display: operation mode, battery charging level, in/out voltage level,• Sound signaling
Main features:	<ul style="list-style-type: none">• Auto restart while AC is recovering• Automatic Voltage Regulator (AVR)• Compatible with power generators• Remote management - UPSmart application included• Built-in EMI, RFI filter• Configurable alarm

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	4.3 kg
Dimensions:	290 x 110 x 145 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

