

Code: UT1050EG-FR/UPS

UPS UT1050EG-FR/UPS 1050 VA CyberPower

Net: 143.32 EUR Gross: 143.32 EUR

The UT1050EG-FR/UPS UPS is a professional device used to maintain the operation of the components connected to it. The UPS UT CyberPower series has been equipped with the best-in-class housing of fireproof plastic, which provides outstanding fire resistance and helps to minimize possible losses in the case of fire.



SPECIFICATION

Nominal power:	630 W
Apparent Power:	1050 VA
Input voltage:	165 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	4 ms
Typical battery charge time:	6 hours
Estimated battery operation time:	<ul style="list-style-type: none">• 65 minutes @ 60 W,• 43 minutes @ 90 W,• 14 minutes @ 200 W
Number of outputs:	4 pcs
Protections:	<ul style="list-style-type: none">• Overvoltage• Overload protection• Overcharge protection• Protection: DSL / Tel / FAX / Modem - RJ11 / RJ45
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling

Main features:	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • Compatible with power generators • Built-in EMI, RFI filter • Configurable alarm
Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	6.79 kg
Dimensions:	95 x 220 x 307 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years

PRESENTATION





Device connectors:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------