

Code: UT650EG-FR/UPS

UPS **UT650EG-FR/UPS** 650 VA CyberPower

Net: **65.91 EUR** Gross: **81.07 EUR**

The UT650EG-FR/UPS UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.



SPECIFICATION

Nominal power:	360 W
Apparent Power:	650 VA
Input voltage:	165 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	4 ms (typical)
Charging time (recover to 90% capacity):	6 hours
Estimated battery operation time:	<ul style="list-style-type: none">• 28 minutes @ 60 W,• 16 minutes @ 90 W
Number of outputs:	3 pcs
Protections:	<ul style="list-style-type: none">• Glass Fuse• Overvoltage• Overload protection• Overcharge protection• Phone/Fax/Modem and RJ11/RJ45 (Combo)/Network protection
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling
Main features:	<ul style="list-style-type: none">• Automatic Voltage Regulator (AVR)• Compatible with power generators• Built-in EMI, RFI filter

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	3.75 kg
Dimensions:	84 x 174 x 280 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------