

Code: VI-1500/R1U

UPS VI-1500/R1U 1500 VA PowerWalker

Net: 501.87 EUR Gross: 617.30 EUR

The VI-1500/R1U UPS is a professional device used to maintain the operation of the components connected to it. The device is mounted to RACK 19" cabinet.



SPECIFICATION

| | |
|--|---|
| Nominal power: | 900 W |
| Apparent Power: | 1500 VA |
| Input voltage: | 165 ... 290 V AC |
| Input frequency: | 45 ... 55 Hz |
| Output voltage: | 230 V AC (Pure Sine Wave) |
| Output frequency: | 50 Hz |
| Voltage adjustment: | ± 10 % |
| Frequency adjustment: | — |
| Transfer time: | max. 4 ms |
| Charging time (recover to 90% capacity): | 8 hours |
| Battery: | 4 x 6V/9Ah |
| Estimated battery operation time: | <ul style="list-style-type: none">• 3.1 minutes @ 100% load• 12.1 minutes @ 50% load |
| Number of outputs: | 4 pcs IEC320 C13 socket |
| Management software: | PowerMaster |
| Protections: | <ul style="list-style-type: none">• Glass Fuse• Overvoltage• Overload protection• EPO (Emergency power off) switch |
| Operation state indication: | <ul style="list-style-type: none">• LCD display: operation mode, battery charging level, in/out voltage level• Sound signaling - with Mute function |
| Main features: | <ul style="list-style-type: none">• "Cold Start" function• Expansion slot• Battery charge and maintenance control• USB/RS-232 communication port |
| Application: | <ul style="list-style-type: none">• Surveillance Systems• data storage centers• network, servers, workstations• Industrial Equipment |
| Housing type: | RACK |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 0 ... 90 % (non-condensing) |
| Weight: | 16.31 kg |
| Dimensions: | 435 x 400 x 44 mm ; RACK 19", 1U |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|-----------------------|-------------|
| Manufacturer / Brand: | PowerWalker |
| Guarantee: | 2 years |

PRESENTATION

Front view:



Rear view:



Expansion slot:



In the kit:



PACKAGE

| | |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|