

Code: UPS02

## UPS **UPS02** 800 VA Green Cell

Net: **61.89 EUR** Gross: **61.89 EUR**

The Green Cell UPS emergency power supply provides full protection for any connected equipment during power loss and voltage spikes. The UPS02 unit is equipped with AGM Green Cell batteries, which provide stable parameters for the equipment.

Original GC UPS software provides comprehensive capabilities to manage the UPS from the computer.



### SPECIFICATION

Power adapter type:	Line-interactive
Nominal power:	480 W
Apparent Power:	800 VA
Input voltage:	162 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 Hz
Transfer time:	2 ... 6 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	4 ... 6 hours
Battery:	1 pcs - 12V/9Ah
Estimated battery operation time:	$\leq$ 20 minutes - depending on the load
Number of outputs:	2 pcs CEE 7/3 (Schuko)
Protections:	<ul style="list-style-type: none"><li>• Short-circuit</li><li>• Overvoltage</li><li>• Overload</li><li>• Overcharge</li><li>• Discharge</li><li>• Overheat</li><li>• Telephone line filter - RJ-11</li></ul>
Operation state indication:	<ul style="list-style-type: none"><li>• LCD display: operation mode, battery charging level, in/out voltage level, Work load, Overload signaling, Failure signaling, Low battery level alarm,</li><li>• Sound signaling</li></ul>

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> <li>• Microprocessor control system</li> <li>• UPS auto diagnostic system</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Auto restart while AC is recovering</li> <li>• "Cold Start" function</li> <li>• Battery charging at power-off mode</li> <li>• Fast intelligent battery recharge function</li> <li>• Remote management - GC UPS application ( Display of operating parameters, schedule, e-mail personal messaging, local access )</li> <li>• USB interface</li> <li>• RESET button</li> <li>• USB A / USB B cable included + Power supply cable</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	4.2 kg
Dimensions:	298 x 101 x 142 mm
Manufacturer / Brand:	Green Cell
Guarantee:	2 years ( 12 months - battery )

## PRESENTATION

Front view:



Rear view:



See the product presentation:

:

In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------