

Code: 12V/2.1A/2.6AH/2.5

UPS 12V/2.1A/2.6AH/2.5 25 W 12 V DC PowerWalker

Net: 38.60 EUR Gross: 47.48 EUR

The UPS is designed for most network devices such as: IP cameras, alarm control panels, smart home management systems and various types of network devices. The device has a small casing, economical design and automatic start in the absence of mains power.



SPECIFICATION

Nominal power:	25 W
Apparent Power:	—
Input voltage:	90 ... 264 V AC
Input frequency:	50 / 60 Hz
Output voltage:	12 V DC \pm 5 %
Connector:	2.5/5.5 mm plug
Charging time (recover to 90% capacity):	3 hours
Estimated battery operation time:	<ul style="list-style-type: none">• 50 minutes - 50% load @ 1 A, 34 minutes (our tests result)• 25 minutes - 100% load @ 2 A, 17 minutes (our tests result)
Battery:	3.7 V / 2.6 Ah
Number of outputs:	1 x 2.5/5.5 mm plug on the cable
Transfer time:	2 ... 6 ms
Operation state indication:	LED diodes
Protections:	<ul style="list-style-type: none">• Overvoltage
Main features:	<ul style="list-style-type: none">• Auto restart while AC is recovering• Power Supply Unit fault indication• Battery charging indication
Dimensions:	108 x 77 x 45 mm
Weight:	0.21 kg
Manufacturer / Brand:	PowerWalker
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PRESENTATION

Device connectors:



In the kit:



OUR OPINIONS



- Easily accessible, inexpensive ICR18650-26F battery allows for independent replacement.



- If the UPS is turned off and there is no access to the 230V mains, it cannot be started.

PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

