

Code: AT-UPS2000-LED

## UPS AT-UPS2000-LED 2000 VA EAST

Net: 162.58 EUR Gross: 162.58 EUR

The AT-UPS2000-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.

The line-interactive power supplies analyse the voltage, frequency and phase shift angle on a current basis, and filter the voltage transmitted to the connected devices. When a mains failure is detected, the UPS immediately switches to autonomous operation mode and continues to power the equipment using the energy accumulated in internal batteries.



### SPECIFICATION

Power adapter type:	Line-interactive
Nominal power:	1200 W
Apparent Power:	2000 VA
Input voltage:	145 ... 295 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	220 / 230 / 240 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Voltage adjustment:	—
Frequency adjustment:	—
Transfer time:	8 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	6 ... 8 hours
Battery:	2 pcs - 12V/9Ah
Number of outputs:	2 pcs CEE 7/3 (Schuko)
Management software:	—
Protections:	<ul style="list-style-type: none"><li>• Glass Fuse</li><li>• Overvoltage</li></ul>
Operation state indication:	<ul style="list-style-type: none"><li>• LED diodes,</li><li>• Sound signaling</li></ul>

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Excellent microprocessor control guarantees high reliability</li> <li>• COLD START function for manual switch to the battery power supply</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Automatic battery charging in OFF mode</li> <li>• self test feature</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• network, servers, workstations</li> <li>• Surveillance Systems</li> <li>• small servers, DVRs, telecommunication equipment, VoIP working hardware, desktop computers, etc.</li> </ul>
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 5 ... 90 %
Weight:	12.2 kg
Dimensions:	380 x 125 x 225 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years

## PRESENTATION

Front view:



Rear view:





In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------