

Code: KIT/NVR1104HS-W-S2/4-F22

SURVEILLANCE KIT **KIT/NVR1104HS-W-S2/4-F22** Wi-Fi, 4 CHANNELS

HDD 1TB - 1080p 2.8 mm IMOU

Net: **237.21 EUR** Gross: **237.21 EUR**

The surveillance kit includes 4 cameras, Wi-Fi IMOU DVR with 1TB hard disk, and 4 power adapters DC 12V/0.5A for independent camera power supply.

Network Video Recorder allowing to operate with Wi-Fi IMOU cameras supported 802.11 b/g/n standards. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m. Camera is according to IP67 Index of Protection norm.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 1080p - 1920 x 1080 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	4 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	Smart H.265+ / H.265 / Smart H.264+ / H.264
Bitrate:	max. 40 Mbps max. 16 Mbps Wi-Fi
Supported hard drives:	• 1 x 8 TB SATA, • HDD : 1 TB (included)
Recording modes:	Manual, Motion Detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback
Network interface:	• 1 x RJ-45 10/100 Base-TX • 2.4 GHz Wi-Fi - IEEE 802.11 b/g/n

Network functions:	- Built-in Wi-Fi module - Imou cameras support : Smart, auto-pairing, Remote configuration, Remote management - Full support via network, Remote records copying, Web Server built-in
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, Alarm Server, P2P
ONVIF:	✓
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) - Android: Free application IMOU - iOS (iPhone): Free application IMOU
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
USB:	2 pcs USB 2.0
Serial ports:	—
Alarm inputs / outputs:	—
PTZ control:	—
Motion Detection:	✓
Intelligent Image Analysis:	—
Main features:	- Smart, auto-pairing < 120 s - Alarm notifications 2x2 MIMO - MIMO technology - increases the throughput of wireless link (multiple antennas transmission) - Operating range in open area : 100 m
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 1.5 A (power adapter included)
Power consumption:	≤ 10 W (without HDD)
Operation temp:	-10 °C ... 45 °C
Weight:	1.3 kg (Recorder with HDD)
Dimensions:	260 x 248 x 48 mm
Supported languages:	Polish, English

CAMERA:

Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm
View angle:	102 °
Range of IR illumination:	30 m



Audio:	• Microphone built-in, • Audio transmission via network
Image compression method:	H.265 / H.264
Main stream frame rate:	25 fps @ 1080p
Network protocols:	TCP, DHCP
ONVIF:	✓
Network interface:	• Ethernet : 100 Mbps • Wi-Fi IEEE 802.11 b/g/n - 2.4 GHz
WEB Server:	—
Mobile phones support:	Access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Main features:	• Wi-Fi module - IEEE 802.11 b/g/n, Range : 50 m (open area) • Motion Detection • People detection • D-ZOOM - Digital Zoom : 16x
Power supply:	12 V DC / 0.5 A (power adapter included)
Power consumption:	< 3.5 W
"Index of Protection":	IP67
Weight:	0.25 kg
Dimensions:	148 x 74 x 74 mm
Supported languages:	—

General information:

Connecting cable:	—
Manufacturer / Brand:	IMOU
Guarantee:	2 years

PRESENTATION

DVR:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Front view:



Rear view:



CAMERA:



Side view:



Memory card slot and "Reset" button:



Camera mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------