

Code: CDP8ACC-ST

DIGITAL DOORPHONE **CDNP8ACC-ST** ACO

Net: **178.93 EUR** Gross: **178.93 EUR**



The CDPN doorphone panels are modern devices with digital dialing of the premises and code-based door opening.

Housing made of aluminum alloy additionally powder coated, provides maximum protection against vandalism and weather conditions.

SPECIFICATION

Compatibility:	ACO CDN
Method of mounting:	Can be flush or surface mounted depending on the frame selected
Operation mode:	Master / Slave
proximity reader built-in:	Unique EM 125kHz
The number of subscribers served:	255 premises
Display:	LCD (heated)
Backlight:	Blue backlight
Inputs:	• 4 x screw connectors - Power connector : AC or DC • 1 x screw connection "INPUT" - External open button NO • 1 x screw connection - connection of audio signal from preceding panel • 2 x „EXTMOD” socket
Outputs:	• 2 x screw connectors „ELOCK” - Connection of a traditional, reversible electric door strike or CDN-PK relay module • 2 x screw connectors - Audio • 2 x screw connectors - connection of a second relay output
Line length:	1000 m (max)
Installation type:	Digital 2-wire

Main features:	• Acoustic and visual signalling of panel functions • Opening the door without answering the call • The control panel can operate either as a Master or as a Slave • Support for up to 1536 keyfobs • Acoustic information in the premises about the opening of the door • Adding and deleting proximity keyfobs with the "master" keyfob (separately for each premise) and with the "super master" keyfob (in all premises) • Ability to connect multiple active receivers under the same number • Porter function • Control of external devices, e.g. entrance gate, barrier, lighting, roller shutters
Power supply:	• 15 V DC / 400 mA or 12 V AC $\pm$ 0.5 V
Power consumption:	~ 6 W
Housing:	Aluminum - powder painted
"Index of Protection":	IP42
Mechanical strength:	IK07
Operation temp:	-20 °C ... 50 °C
Weight:	0.450 kg
Dimensions:	205 x 90 x 32 mm
Manufacturer / Brand:	ACO
Guarantee:	2 years

PRESENTATION

Rear view:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------